



DRY TONER

185HWLD

Matt White Film

- Performance grade for cost conscious applications
- Matt white opaque suitable for full colour duplex printing
- Waterproof, tear-proof, greaseproof, can be hole punched
- Ideal for documents where strength & light weight are required
- No need to laminate

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (185µ/7.3mil) Weight (263gsm)

Kernow Coatings Ltd	www.kernowcoatings.com
Kernick Road	sales@kernowcoatings.com
Penryn, Cornwall	_
TR10 9DQ	T: +44 (0)1326373147
United Kingdom	F: +44 (0)1326376614

Registered in England
No. 1092182
A Member of the Sensitisers
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitisers Group 2016





340HWLD

Matt White Film

- Performance grade for cost conscious applications
- Matt white opaque suitable for full colour duplex printing
- Waterproof, tear-proof, greaseproof, can be hole punched
- Ideal for documents where strength & light weight are required
- No need to laminate

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (340µ/13.4mil) Weight (491gsm)

Kernow Coatings Ltd Kernick Road Penryn, Cornwall TR10 9DO	www.kernowcoatings.com sales@kernowcoatings.com T: +44 (0)1326373147
TR10 9DQ	F: +44 (0)1326373147
United Kingdom	F: +44 (0)1326376614

Registered in England
No. 1092182
A Member of the Sensitisers
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitisers Group 2016





135HWLD

Matt White Film

- Performance grade for cost conscious applications
- Matt white opaque suitable for full colour duplex printing
- Waterproof, tear-proof, greaseproof, can be hole punched
- Ideal for documents where strength & light weight are required
- No need to laminate

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (135µ/5.3mil) Weight (190gsm)

Kernow Coatings Ltd Kernick Road Penryn, Cornwall TR10 9DQ	www.kernowcoatings.com sales@kernowcoatings.com T: +44 (0)1326373147
United Kingdom	F: +44 (0)1326376614

Registered in England
No. 1092182
A Member of the Sensitisers
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitisers Group 2016





240HWLD

Matt White Film

- Performance grade for cost conscious applications
- Matt white opaque suitable for full colour duplex printing
- Waterproof, tear-proof, greaseproof, can be hole punched
- Ideal for documents where strength & light weight are required
- No need to laminate

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (240µ/9.4mil) Weight (344gsm)

Kernow Coatings Ltd	www.kernowcoatings.com
Kernick Road	sales@kernowcoatings.com
Penryn, Cornwall	T: +44 (0)1326373147
TR10 9DQ	
United Kingdom	F: +44 (0)1326376614

Registered in England No. 1092182 A Member of the Sensitisers **Group of Companies**

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitisers Group 2016