

Mastertac Technical Information

24-06-2025 EN SI

Product **NATURLASER M HS-FSC / PERM DIGITAL / KRAFT 90 / SCORE UNPRINTED**

Sales Code FMD/94-P/39/W2

Product use Recycled product designed for multipurpose labeling in logistics and retail end-uses requiring variable information printability such as direct mailing, business forms, shipping labels, on laser applications with excellent lay-flat properties.

Typical technical values

Face **NATURLASER M-FSC**

Product White uncoated paper made from 100% recycled fibres.

Substance 80 g/m² ISO 536

Caliper 105 µm ISO 534

Tensile strength MD 3,9 kN/m ISO 1924/2 min

Tensile strength CD 1,8 kN/m ISO 1924/2 min

Smoothness 25 Bekk sec ISO 5627 min

Opacity 87 % ISO 2471

CIE Whiteness 140 % ISO 11475

Printability Flexography, letterpress and offset. It is also inkjet and laser-copier printable.

Sustainability The product is sold as FSC™ Recycled Credit under UPM Raflatac's FSC certificate SG SCH-COC-004879.

Adhesive **PERM.DIGITAL**

Type Permanent

Composition Waterborne acrylic

Tack min 10 N FTM 9

Shear min 2 h FTM 8

Backing **KRAFT 90**

Product White woodfree kraft backing paper.

Substance 86 g/m² ISO 536

Caliper 87 µm ISO 534

Tensile strength MD 6,5 kN/m ISO 1924

Tensile strength CD 3 kN/m ISO 1924

Performance

Total caliper 204 µm ± 10%



Mastertac®
by UPM Raflatac

Minimum labelling temperature	5°C
Service temperature	-10 to 100°C
Shelf life	From date of manufacture: 48 months, under FINAT defined storage conditions (+20-25°C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.
Information	
Product Information	Scoring is crucial to ensuring self-adhesive labels are easily peeled away from their backing. Our sheets have folding scores that are spaced at 35 mm intervals, what enables a smooth label opening. Scores open after bending 90-120° Scores don't open if they have not been folded previously.
Product availability	Standard range. (Other sizes and/or components available upon request).

STANDARD SHEET SIZE (CM)	32 x 45
PACKAGING TYPE	Box 100 sh

Approvals

Approvals	Toy labeling: This product complies with the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements.
Disclaimer	The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.